



easyFILL 6 µm - M 10 x 1 10 x FFG-PZ-MU-MAGN

Item number:	14 610 101
EAN:	4103810704970
Discount group:	A

Technical data Grease gun connection, pressure-side: Capacity (cm3): Refilling options: Diameter of grease piston (mm): 10 Grease pump piston actuation: Delivery rate/stroke (cm³): 2,2 Discharge pressure up to (bar): 400 Burst pressure system (bar):

Burst pressure grease gun head (bar):

M 10 x 1 400 400 g grease cartridge, DIN 1284 (12 511), (12 514) manually lever operated 900 1200 Wall thickness of grease gun tube (mm): 1 black 380 x 185 x 66 1.02

Specification

Weight (kg):

- With magnet
- With hose bracket

Grease gun tube colour:

Dimensions LxWxH (mm):

- Follower plates, 10 pieces (14 900)
- High pressure hose, M 10 x 1 male, 11 x 600 mm, with sealing ring (12 880 828)
- Precision machined coupler, 4 claws, M 10 x 1 female (12 643)
- Grease gun head, zinc die casting Z 410
- Ball seat valve, galvanized (85 589)
- Ergonomic handle, non-slip, excellent power transfer and handling

Special notes

- Operates with NLGI 2 greases
- Quantity of delivered grease at a back-pressure of 200 bar nearly unchanged after 40,000 operating cycles
- Pump piston and cylinder with 6 µ fit (no dummy lubrication)
- Thanks to the optimized hand lever kinematics, lubrication can be done with little effort
- The ease of dismantling permits simple cleaning
- Rolled thread on the grease gun tube resists damage from impact and allows quick and easy screwing-in by 1,5 turns
- High-speed ventilation, by half a rotation of the grease gun tube
- Designed for use in rough conditions
- Similar to DIN 1283

Packaging

Dimensions LxWxH (mm):	395 x 150 x 70
Weight including package (kg):	1,14
Packing unit:	1,0