

1.07/K-1-SE 200 S

Puller-Set

with 6 legs

Code	ETIM
1745158	EC011834 Abzieher-/Gleithammer-Set
EAN	UNSPSC
4036976112825	27-11-17-12 Abzieher
Country of origin	eCl@ss
Germany	21-04-15-01 Abziehvorrichtung
Customs tariff number	
82055980	



Article description

- The forged leg feet are very slim particularly suitable for barely accessible places
- Quick release legs for fast, easy set-up and adjustment
- Contents: 2 spindles, 1 cross-beam each 2- and 3-arm pattern, and 6 slim quick-release pulling legs in 2 lengths
- Clamping reach 100 mm = thickness of hooked foot at tip (e) 3.7 mm, max. 2.5 t
- Clamping reach 200 mm = thickness of hooked foot at tip (e) 2.0 mm, max. 2.0 t
- Clamping depth 200 mm = hook foot thickness (e) 2.0 mm, max. 2.0 t

Article parts list

106/203 Cross beam 2-arm 220 mm, 107/203 Cross beam 3-arm 220 mm, 106/A-100-SE Pull-off hook with quick release clamping piece 100 mm (3x), 06/S-200-SSE Slim pull-off hook with quick release clamping piece 200 mm (3x), E-1.1406140 Spindle 17, M14x1.5, 140 mm (2x), 107/199-SE 200S Plastic case with foam insert for 1.07/K-1-SE 200S

Article information

Clamping width (max.) external pulling [mm]	90 mm	Quick release lever available	yes
Spindle thread size	M14x1,5 x 140	3D data available	no
Contents (Qty of pieces)	9	Spindle anti-slip device	no
Width of hooked foot [mm]	27 mm	Screws included	no
Usable depth of hooked foot d2 [mm]	7,5 mm	Anti-slip device on the spindle	no
Thickness of hooked foot at tip	3,7 mm	Swivel hook	no
Width across flats [mm]	17 mm	Can be retrofitted with hydraulic spindle	no
Tractive force (max.) [t]	2,5	Version/Execution	In robust plastic case
reversible arms available	no	Graduation	no
Clamping bracket available	no	Exchangeable spindle tip	no
REACH registration available	no	Usable clamping reach	100 - 200 mm
Net weight [kg]	4,2 kg	Tractive force (max.) ≥ [t]	2,0
Hook brake available	no	Hook foot thickness at the tip ≥ e1 [mm]	2,0 mm
Hook can be moved parallel	no		